



2444 Baldwin Road ■ Cleveland, OH 44104

1-800-662-6338 ■ PH: 216-231-8590 ■ FAX: 216-231-2702 ■ www.plasticsafety.com

Plastic Safety Systems FHWA / WZ Approval List As of 03/27/07

- WZ-3** Generic Drum approval
- WZ-54** Generic Drum approval with Light attached.
- WZ-61** 12/13/00
“PST-III” Type III Barricade:
With 8’ extruded boards. Centerboard spacing @ 16.25” on center.
- WZ-85** undated
FHWA Policy Memo: Sign Stands, Substrates, generic Type-III Barricade:
- Light attachments:**
1 or 2 lightweight warning lights attached to the backside of the vertical up-rights. Or removable head lights.
- Plastic Centerboards:**
Limited to a maximum of 8’
- Sign Attachments:**
These include Lightweight or Roll-up signs, mounted on or above the top rail.
Top of the sign must be a minimum of 87” to the top of the sign.
- WZ-102** 4/12/02
“PST-III” Type-III Barricade:
Already with 8’ extruded boards.
Added Warning Lights.
With centerboard spacing changed to 20” on center.
- Life Vest:** Complete system.
- Navigator Vertical Panel:**
With or without Light attached 30 lb rubber base
Panel sizes – 12x36, 12x24, 8x36, 8x24
- “F & A Frame”:**
With or without Light attached
With or without up to 25 lbs of sand per leg
Centerboard lengths – 12’, 10’, 8’, 6’, 4’
Other centerboard designs i.e. – “I-beam” Foamed 2x8
- WZ-152** **“Anchor” Type-III:** 4/10/03
with 8’ boards, ballasted with 45 lbs of sand per side.
The Anchor feet replaced the “PST-III” skid configuration.